

# prepworx™ Unglu'd Adhesive & Mastic Remover

Universal adhesive & mastic remover for pressure-sensitive adhesives (PSAs) and other flooring mastics, glues, and adhesives (both water-based and non-water-based).

## Style Name

## Style Number

Unglu'd—4 Gallon

321CA

### Features + Benefits:



Eliminates the need for time-consuming mechanical or abrasive removal, as well as the use of toxic chemicals



Non-toxic and fully biodegradable



Single component adhesive remover



Minimum of 2 hour dwell time, and up to 24 hours (overnight)



Will not affect the bond of new adhesive applications when used properly



#### Spread Rate:

#### Application Method

Medium nap-roller, brush, or other spreading technique

#### Coverage

100 sf/gallon

### Product Characteristics

Weight	55 lbs. / 4 gallon pail
Pallet Quantity	36
Pallet Weight	2020 lbs
Polymer Type	Single component adhesive remover
VOC's (Rule #1168 of California SCAQMD)	<0 g/L
Color	Tan
Shelf Life	1 year from manufacturing date in an unopened container
Storage Conditions	50°–80° F (15°–27° C). Protect from freezing
Cleaning Instructions	Tools and surfaces can be cleaned with water. Dispose of excess material in accordance with local, state, and federal regulations
Traffic	N/A. This is a removal product, not a permanent floor product.
Dry Time	The dwell time is about 2 hours (from placement to glue removal)
Working Time	24 hours
Warranty	Shaw Industries warrants that Unglu'd will be free from manufacturing defects when used within the shelf life of the product.

For more information about *Unglu'd*, contact your local Shaw Contract account manager, visit us at [shawcontract.com](http://shawcontract.com) or call 1.800.257.7429.

[ totalworx ]

ShawContract®